

Project Overview



Talon Nickel (USA) LLC (Talon) is proposing to construct an underground mine for the extraction of nickel and copper ore in Aitkin County, Minnesota. The mined rock would be transported by rail to a facility in Mercer County, North Dakota for ore processing and tailings disposal.

Where would the proposed Tamarack Nickel project be located?

The proposed Tamarack Nickel project (Project) would be located approximately 1.5 miles north of the city of Tamarack, Minnesota, 30 miles west of Cloquet, Minnesota, and 10 miles east of McGregor, Minnesota. The project seeks to target minerals within the Tamarack North Resource, which is part of the Tamarack Intrusive Complex. The proposed mine would be in the greater Mississippi River Watershed.

What are the typical phases of a mining project like the Tamarack Nickel proposal?

The Project will first require mandatory preparation of a State Environmental Impact Statement (EIS) and issuance of various state, federal, and local permits. No permit applications have been submitted by Talon, and no permit decisions or other approvals may be authorized until the EIS process is complete and deemed adequate.

If the proposed project ultimately receives all permits and approvals, there will be three major phases:

- **Pre-mining construction** would include land-clearing, construction of new buildings, mine access portals, transport facilities and other structures, and utility upgrades.

- **Mining operation** would last approximately 8-10 years and would include mining, rail loadout, water treatment, and backfill materials placement and management.
- **Closure and post-closure maintenance** would occur after mining ends at the facility, including timely reclamation as required by Minnesota statute and rule. The Project would require financial assurance under a permit to mine.

How does Talon propose to approach mining and waste management?

Talon proposes to mine using a combination of underground methods, including the use of a tunnel boring machine, probe drilling, blasting, and resource extraction. During the mine's proposed 8-10-year operational life, backfill would be placed in the underground mine works to fill voids created by the mining operations and provide structural stability. Each mined area would be backfilled with a blend of cement and crushed rock (similar to concrete) before moving to the next location. Mining would be done 500 to 1500 feet below the ground surface, in the underlying bedrock. Talon proposes to build a rail spur to connect the project site to the existing Burlington Northern Santa-Fe railway located south of the proposed surface operation. Talon estimates a train between 40 and 100 cars would leave the site every 2 to 7 days to transport the mined ore to the North Dakota site.

For additional information about the proposed project, visit the Talon Metals LLC Website, talonmetals.com.

Disclaimer: This document is a working document. This document may change over time as a result of new information, further deliberation, or other factors not yet known.