Prepared and published with the support of the MINNESOTA ENVIRONMENT AND NATURAL RESOURCES TRUST FUND and the CLEAN WATER, LAND, AND LEGACY AMENDMENT

COUNTY ATLAS SERIES ATLAS C-19, PART B, PLATE 10 OF 10 Sensitivity of Groundwater Systems to Pollution







POLLUTION SENSITIVITY OF THE NEAR-SURFACE MATERIALS, BURIED SAND AND GRAVEL AQUIFERS, AND **BEDROCK AQUIFERS**

Bv

James A. Berg





FIGURE 2. Geologic sensitivity rating for the buried sand and gravel aquifers and the bedrock aquifers as defined by vertical travel time (Geologic Sensitivity Workgroup, 1991). Ratings are based on the time range required for water at or near the surface to travel vertically into the groundwater of interest or a pollution sensitivity target. Tritium and carbon-14 studies indicate the relative ages of groundwater.







MAP EXPLANATION

Figures 3–8

Pollution sensitivity rating

Estimated vertical travel time for water-borne contaminants

to enter an aquifer (pollution sensitivity target).

VH Very High—Hours to months.

M Moderate—Years to decades.

L Low—Decades to a century.

VL Very Low—A century or more.

H High—Weeks to years.



FIGURE 7. Pollution sensitivity of the stw and su buried sand aquifers; su aquifer unless labeled otherwise.

Sampled well and aquifer symbols

Buried sand and gravel aquifers

🛆 sm

sc1

• sts

🗙 stw

💼 su

Bedrock aquifers

▲ Hinckley sandstone

Fond du Lac Formation

Precambrian crystalline bedrock

sic



Groundwater conditions

grained material to an underlying aquifer.

② Groundwater recharge from overlying surficial

(3) Groundwater leakage from an overlying buried

(4) Groundwater leakage through multiple aquifers and

Unknown source of recent or mixed groundwater.

aquifer to an underlying buried aquifer.

aquifer to buried aquifer.

fine-grained layers.

Lateral groundwater flow.

(1) Infiltration through a thin layer of overlying, fine-

FIGURE 9. Generalized cross section showing recharge concepts for buried aquifers considered in the sensitivity evaluations. In this model, all recent recharge enters the buried aquifer system at recharge surface 1 (red dotted line). Recharge surface 1 is considered to be at the land surface where till is present or at the bottom of surficial sand deposits. If less than 10 feet of fine-grained sediment (clay or till) exists between recharge surface 1 and the shallowest underlying buried aquifer, then recent recharge is assumed to reach and move to the bottom of the aquifer which is defined as recharge surface 2. A second deeper buried aquifer that has less than 10 feet of clay or till between it and the overlying buried aquifer is also assumed to allow further penetration of recent recharge. In that case, recharge surface 3 is defined at the bottom of this next deeper aquifer. The pink arrows indicate groundwater recharge of recent tritium age through a recharge surface.

Thickness of protective layer between the aquifer and the nearest overlying recharge surface (in feet) Greater 0 to 10 10 to 20 20 to 30 30 to 40 than 40



FIGURE 10. Pollution sensitivity rating matrix. Pollution sensitivity is inversely proportional to the thickness of a protective laver between the top of the aquifer and the nearest overlying recharge surface as defined in Figure 9. Any buried aquifer with less than a 10-foot-thick protective layer between it and an overlying recharge surface is rated very high sensitivity because there is little fine-grained material above it to retard downward groundwater movement. A thicker overlying protective layer provides additional protection to the aquifer, and sensitivity ratings are assigned based on the thickness of this layer. In areas where the depth from the land surface to the top of the aquifer exceeds 100 feet, the very high and high classifications may be overestimates if vertical gradients and hydraulic conductivities are low.

INTRODUCTION

This plate describes the sensitivity to pollution of the buried sand and gravel aquifers, the bedrock aquifers in the study area, and of the near-surface materials by estimated infiltration travel time of a contaminant that moves conservatively with water. For the purpose of this study, the nearsurface is defined as land surface to a depth of 10 feet.

Migration of contaminants dissolved in water through unsaturated and saturated sediments is a complex process. It is affected by biological degradation, oxidizing or reducing conditions, contaminant density, and other factors. Large-scale assessments of pollution sensitivity require some generalizing assumptions. For example, flow paths from the land surface through the soil and underlying sediments to an aquifer are assumed to be vertical; horizontal flow paths may be important in specific instances, but they have not been adequately mapped and are not considered in this sensitivity model. Permeability of the sediments is evaluated only qualitatively. The sensitivity assessment is an empirical method that estimates the time of travel for water from infiltration at the land surface to the pollution sensitivity target.

The geologic sensitivity rating of the near-surface materials (Figure 1) shows geologic sensiburied sand and gravel aquifer maps (Figures 6, 7, and 8) are unchanged from corresponding geologic tivity corresponding to an estimate of travel time from the land surface to a depth of 10 feet. The focus of this near-surface sensitivity rating estimate is travel in the vadose zone, which is the unsaturated zone between the land surface and the water table. The time of travel through this thin surface layer in the study area varies from hours to approximately a year. Areas with relatively short travel times low or very low.

Figure 2 shows the rating for geologic sensitivity that corresponds to an estimate of travel time to mapped buried sand and gravel aquifers and bedrock aquifers. The aquifer sensitivity rating has the same categories as the near-surface sensitivity rating, but the ratings represent significantly longer two sensitivity ratings are shown in different colors.

three-dimensional geographic information system (GIS) surfaces. The second step is representing aquifer recharge as a series of related elevation surfaces that can be used along with the protective layer thickness calculations. The third step is interpreting the protective thickness calculations as pollution sensitivity.

Tritium age

Color indicates tritium age of water sampled in well.

Recent—Water entered the ground since

less than or equal to 1 TU).

about 1953 (10 or more tritium units [TU]).

Mixed—Water is a mixture of recent and vintage

waters (greater than 1 TU to less than 10 TU).

Vintage—Water entered the ground before 1953

The geologic maps and associated stratigraphic information created for Plates 3, 4, and 5 of Part A were the basis for all the hydrogeologic maps and cross sections shown in this Part B and represent the first step of the pollution sensitivity modeling process. For this report, some of the information from Part A was reclassified and reinterpreted to separate the surficial water table aquifer from the buried sand and gravel units that are most commonly treated as hydrologically confined aquifers. Thus, the extent and thickness of sand and gravel units Qsm, Qsl, and Qsc shown in Figures 5, 6, and 7, respectively, on Plate 5 of Part A have been modified. These three geologic map units are shown in this report as the less extensive corresponding buried sand and gravel aquifers sm, sl, and sc; the surficial portions of these units have been reclassified and incorporated into the surficial sand aquifer map. In addition, the sc1 aquifer (Figure 5) that had not been mapped as part of the set of sand and gravel units on Plate 5 of Part A was mapped for this report as an additional buried aquifer. The remaining

map units in Part A. The relationship between geologic map units and aquifers is illustrated in Figure 2 on Plate 8

Once these modifications to the digital maps were completed, a method using threedimensional GIS surfaces that has been used for previous atlases (Berg, 2006; Tipping 2006; Petersen, (hours to weeks) are rated high or very high. Areas with longer travel times (months to a year) are rated 2007; Berg, 2008; Peterson, 2010) was used to create the pollution sensitivity evaluation shown on this plate. This model predicts how water from precipitation, which first infiltrates the surficial aquifers,

directly recharges portions of the first underlying aquifer and, subsequently, portions of deeper aquifers. The central concept of the model is focused recharge, or relatively rapid recharge. In focused recharge, portions of the aquifers overlap and are connected by complex three-dimensional pathways travel times; to distinguish the ratings applied to these two different pollution sensitivity targets, the that allow surface water to penetrate into even the deepest mapped aquifers in some areas. The sensitivity model for the buried aquifers simplifies this concept by dividing focused recharge into discrete surfaces at the base of each aquifer, which are called recharge surfaces (Berg, 2006). Each buried aquifer receives focused recharge from the base of the overlying aquifer if the confining layer separating those aquifers is thin or absent. For the purposes of this model, a thin protective layer is considered to

or less), recent or mixed water infiltrates to the next underlying aquifer and so on until a limited amount of recent or mixed water reaches recharge surface 3 for the deepest aquifer. Just as the aquifer and till layer surfaces were created as elevation grid layers, the recharge surfaces were also created in this same GIS file format. Each recharge surface was produced through a series of GIS calculations starting with the land surface elevation grid and proceeding stepwise downward to the top of the lowest mapped aquifer. With each succeeding step, the deepest portion of the recharge surface becomes progressively smaller, thereby mimicking a general reduction of recharge with depth that occurs in the natural system.

next underlying aquifer (pink arrow) and moves downward to recharge surface 2 (black dotted line).

If the same criteria are applied at recharge surface 2 (underlying protective layer thickness of 10 feet

The calculated elevation surfaces for all the aquifers and recharge surfaces are used in the third step to generate pollution sensitivity maps for each buried aquifer. In the final step of the sensitivity evaluation, the thickness of the protective till or aquitard that covers each aquifer is calculated and a sensitivity rating is applied. The sensitivity of the aquifer is inversely proportional to the thickness of that protective layer. The protective layer thickness is calculated by subtracting the elevation of the top of the aquifer from the elevation of the adjacent overlying recharge surface. Figure 10 shows the rating matrix for interpreting the pollution sensitivity of the buried aquifers according to the calculated protective layer thickness. The resulting pollution sensitivity evaluations for each buried sand and gravel aquifer are shown on Figures 3 through 7. The same process was conducted to produce the bedrock aquifers pollution sensitivity map in Figure 8.

Comparison of Sensitivity Model to Groundwater Chemistry Data from the Buried Sand Aquifers

The results of a valid pollution sensitivity model should generally correspond to the distribution of groundwater residence time indicators. The most important indicators for the buried aquifers were the values and spatial characteristics of tritium in collected groundwater samples. In general, the groundwater samples with recent and mixed tritium age should correspond to areas of very high to

mixed tritium age and are consistent with the pollution sensitivity ratings with the exception of three samples with recent tritium age from the sc aquifer (one sample east of Scanlon, and two samples southwest of Wrenshall) in an area of the sc aquifer rated very low sensitivity. Lateral groundwater movement from nearby recharge areas or well construction problems may account for these inconsistencies. Most of the groundwater samples from this aquifer that had recent and mixed tritium age also had elevated Cl/Br values consistent with contaminant sources. The ¹⁴C residence time of 3000 years

(D) Groundwater discharge from a buried aquifer to surface-water body.

of the sample east of Barnum is consistent with the very low sensitivity rating in that area Similar to the previously described aquifers, the sc1 aquifer shows a mixture of sensitivity ratings from very high to very low (Figure 5). Most of the groundwater samples with recent and mixed

tritium age in the western part of the study area associated with moderate to very high sensitivity ratings are due to infiltration through thin overlying fine-grained layers (glacial till). The groundwater sample with recent tritium age west of the Kettle River is in a portion of the sc aquifer rated very low sensitivity and may be due to poor well construction. The two groundwater samples collected from the south-central portion of the study area show that local variations in the overlying stratigraphy can have a significant effect on groundwater residence time. The recent tritium age of the western sample is likely due to infiltration through overlying sand layers. In contrast, just over a mile to the east of the recent-age sample, a water sample from the aquifer had vintage tritium age and had a ¹⁴C groundwater age of 6000 years.

The pollution sensitivity of the sic and sts aquifers is shown on Figure 6. Most areas of both aquifers have a very low sensitivity rating due to greater depth of burial and lack of overlying surficial sand. Two groundwater samples were collected west of Eagle Lake (located in the western part of Carlton County and the left side of cross section E-E'). The sample from the shallower sic aquifer had a recent tritium age and the sample from the deeper sts aquifer had vintage tritium age. The seven

across this more sensitive area near rivers and streams, groundwater samples of mixed and vintage tritium age indicate probable upwelling conditions or groundwater discharge locations (condition labeled as D) as deeper, older water is brought to the surface by upward gradients. Samples with recent or mixed tritium age that do not match the local pollution sensitivity ratings, such as groundwater samples of recent tritium in low to very low sensitivity areas, are probably due to lateral groundwater movement (condition \square).

REFERENCES CITED

Berg, J. A., 2006, Geologic atlas of Pope County, Minnesota: St. Paul, Minnesota Department of Natural Resources County Atlas Series C-15, Part B, 4 pls., scale 1:100,000. Berg, J. A., 2008, Regional hydrogeologic assessment, Traverse-Grant area, west-central Minne-

sota: St. Paul, Minnesota Department of Natural Resources Regional Hydrogeologic Assessment Series RHA-6, Part B, 4 pls., scale 1:250,000. Geologic Sensitivity Workgroup, 1991, Criteria and guidelines for assessing geologic sensitivity of ground water resources in Minnesota: St. Paul, Minnesota Department of Natural Resources,

Division of Waters, 122 p. Natural Resources Conservation Service (NRCS), 2006, Soil survey geographic database for St. Louis County, accessed at http://soildatamart.nrcs.usda.gov/ssurgometadata.aspx>.

Natural Resources Conservation Service (NRCS), 2009a, Hydrologic soil groups, Chapter 7, accessed at <http://directives.sc.egov.usda.gov/OpenNonWebContent.aspx?content=22526.wba>. Natural Resources Conservation Service (NRCS), 2009b, Soil survey geographic database for Carlton County, accessed at http://soildatamart.nrcs.usda.gov/ssurgometadata.aspx>. Petersen, T.A., 2007, Geologic atlas of Crow Wing County, Minnesota: St. Paul, Minnesota Depart-

samples with mixed tritium age in the north central and northeastern parts of the study area reflect a range of conditions including infiltration through thin overlying protective layers (groundwater condition (1), lateral groundwater movement from nearby recharge areas (condition (1)), and leakage from Petersen, T.A., 2010, Geologic atlas of Todd County, Minnesota: St. Paul, Minnesota Department the surficial aquifer (condition 2).

The buried sand and gravel aquifer and the bedrock aquifer sensitivity ratings are based on vertical travel times defined by the Geologic Sensitivity Workgroup (1991). The travel times to these aquifers vary from days to thousands of years. Areas with relatively short travel times of less than a few years are rated high or very high. Areas with estimated travel times of decades or longer are rated be 10 feet or less in thickness. low or very low.

SENSITIVITY TO POLLUTION OF THE BURIED SAND AND **GRAVEL AQUIFERS AND THE BEDROCK AQUIFERS**

Development of Sensitivity Model and Maps

The pollution sensitivity modeling and mapping process involved calculating the thickness of protective material overlying each aquifer and interpreting protective thickness as different levels of pollution sensitivity. The pollution sensitivity modeling and mapping process has three steps. The first step is mapping and defining the aquifers and the protective layers for the underlying aquifers as

The vertical recharge path of water for a stack of aquifers typical of the study area is shown in Figure 9. The figure shows a generalized cross section of the principal aquifers mapped in a portion of the study area. Similar stacks of different aquifer combinations exist throughout the study area. The vertical path of water from precipitation at the land surface to buried aquifers crosses recharge surfaces of the buried aquifers. In Figure 9, the recharge surfaces are labeled 1 (generally shallow), 2 (generally intermediate depth), and 3 (generally deep). In this conceptual model, all the recent recharge water

enters the buried aquifer system (pink arrow) at recharge surface 1 (red dotted line). In thick sand and gravel areas, the generally shallow recharge surface 1 is at the base of the sand and gravel. Where little or no sand or gravel exists at the surface, recharge surface 1 is the same as the land surface. If the protective, low permeability layer (till or clayey lake sediment) between the base of recharge surface 1 and the top of the underlying buried aquifer is 10 feet or less, recent recharge water infiltrates to the

of low to very low sensitivity. The ¹⁴C residence time values from collected groundwater samples were also useful for corroborating sensitivity ratings for portions of the buried aquifers that have a predicted very low sensitivity. The chloride to bromide (Cl/Br) ratios as an anthropogenic (created by humans) indicator of recent industrial age activity were useful evidence of recent water infiltration and an evaluation tool for areas with very high to low pollution sensitivity ratings.

Buried sand and gravel aquifers. The sm and sl aquifers are both shown on Figure 3. Moderate to very high sensitivities are very common for both of these aquifers due to generally shallow conditions and overlying surficial sand in many areas. Only one groundwater sample was collected from the sm aquifer located southwest of Wrenshall. The vintage tritium age of the sample at that location is consistent with the associated very low sensitivity rating.

Moderate to very high sensitivities were also common along the northwestern edge of the sc aquifer (Figure 4) extending from south-central to northeast Carlton County where the aquifer is typically shallower and overlain by surficial sand. Most of the groundwater samples had recent and surficial sand aquifer to the bedrock aquifers is evident (conditions (2) and (3)). At several locations

Symbols and labels

• Groundwater sample from spring collected for

2000 If shown, groundwater age in years, estimated

Major bedrock aquifer contact (Figure 8 only).

by carbon-14 (¹⁴C) isotope analysis.

chemical analysis; color indicates tritium age.

• If shown on well symbol, chloride to

bromide ratio greater than 190.

× Well log used to map aquifer

← Groundwater flow direction

Extent of surficial sand aquifer.

F F' Line of cross section.

Body of water.

The stw and su aquifers (Figure 7) generally have very low sensitivity ratings due to thick moderate sensitivity, and the groundwater samples of vintage tritium age should correspond to areas overlying protective layers. Most of the areas rated moderate to very high sensitivity are in the eastern part of the study area where the su aquifer is overlain by thick surficial sand. Apparent lateral groundwater flow from nearby recharge areas accounts for several samples with recent and mixed tritium age in the eastern part of the study area. A sample with recent tritium age collected from a location in the southwestern part of the study area may represent another example of this condition.

> Bedrock aquifers. Shallow bedrock conditions, with depth to bedrock of less than 150 feet is very common in the study area with the exception of the deep bedrock valley in the southeastern part of the study area and portions of the northwestern study area. Most of the area of the bedrock aquifer rated moderate to very high sensitivity has generally shallow bedrock conditions and consequently limited overlying protective layers. The most common infiltration condition in the southwestern part of the more sensitive area is infiltration through a thin layer of overlying, fine-grained material to an underlying layer (condition 1). In the northeastern part of this area, where shallow bedrock conditions coincide with the presence of surficial and buried aquifers, direct and indirect recharge from the Agency

ment of Natural Resources County Atlas Series C-16, Part B, 4 pls., scale 1:100,000. of Natural Resources County Atlas Series C-17, Part B, 4 pls., scale 1:100,000. Tipping, R. G., 2006, Subsurface recharge and surface infiltration [Plate 6], in Geologic Atlas of Scott County, Minnesota: Minnesota Geological Survey Atlas Series C-17, Part A, 6 pls., scale 1:150,000

ACKNOWLEDGMENTS

The author wishes to thank the following people for their assistance in the production of this atlas: Jim Walsh, Minnesota Department of Health; Bob Tipping and Alan Knaeble, Minnesota Geological Survey; Scott Alexander and Calvin Alexander, University of Minnesota, Department of Geology and Geophysics; Nancy Schuldt, Fond du Lac Band of Lake Superior Chippewa; Heather Cunningham, Carlton County; Jan Falteisek, Neil Cunningham, Greg Massaro, Shana Pascal, Todd Petersen, Jeremy Rivord, and Jeanette Leete of the Minnesota Department of Natural Resources; Melinda Erickson, U.S. Geological Survey; and Andrew Streitz, Minnesota Pollution Control





of Natural Resources is available regardless of race, color, national origin, sex, sexual orientation, marital status, status with regard to public assistance, age, or disability. Discrimination inquiries should be sent to Minnesota DNR, 500 Lafayette Road, St. Paul, MN 55155-4031, or the Equal Opportunity Office, Department of the Interior, Washington

© 2011 State of Minnesota. epartment of Natural Resources, and the Regents of the University of Minnesota.

This map was compiled and generated using geographic information systems (GIS) chnology. Digital data products, including chemistry and geophysical data, are available from DNR at http://www.dnr.state.mn.us/waters.

This map was prepared from publicly available information only. Every reasonable effort as been made to ensure the accuracy of the factual data on which this map interpretation is based. However, the Department of Natural Resources does not warrant the accuracy ompleteness, or any implied uses of these data. Users may wish to verify critical information ion; sources include both the references here and information on file in the offices of the Ainnesota Geological Survey and the Minnesota Department of Natural Resources. Ever effort has been made to ensure the interpretation shown conforms to sound geologic and cartographic principles. This map should not be used to establish legal title, boundaries, or Base modified from Minnesota Geological Survey, Carlton County Geologic Atlas, Part A,

Project data compiled from 2009 to 2010 at a scale of 1:100,000. Universal Transverse Mercator projection, grid zone 15, 1983 North American datum. Vertical datum is mean sea

GIS and cartography by Jim Berg, Greg Massaro, and Shana Pascal. Edited by Neil



TABLE 1. Infiltration rates used to assess pollution sensitivity rating of near-surface materials. Minimum transmis-
sion rates for NRCS hydraulic groups (2009a) and surficial geology map units are from Tipping (2006) using similar ranges of soil and sediment textures.

NRCS hydraulic group rating	Texture	Minimum transmission rate (inches per hour)	Surficial geology map unit (Plate 3 of Part A)	Texture	Minimum transmission rate (inches per hour)
A, AD	muck, sandy Ioam, Ioamy sand	0.3	Qai, Qao, Qci, Qco, Qd, Qli, Qlo, Qmi, Qmo, Qt, Qwg	sand and gravel	0.5
B, BD	sandy Ioam, silt Ioam	0.15	Qal, Qcc, Qct, Qha, Qit, Qll, Qws	sandy loam	0.3
C, CD	loam, very fine sandy loam, silt loam, fine sand	0.05	Qhp, Qlc, Qlt, Qul, Qac, Qmc	loam to silty loam, peat	0.15
D	clay, loam, fine sandy loam, peat, silty clay	0.01	Qab, Qat, Qmt, Qmw	loam to clay loam	0.05
			Qkt, Qwf	clay loam	0.01

SENSITIVITY TO POLLUTION OF THE NEAR-SURFACE MATERIALS

The sensitivity to pollution assessment for near-surface materials estimates the time of travel for water to travel from the land surface to a depth of ten feet, and is shown in Figure 11. Soil properties are used to estimate the travel time from land surface to a depth of three feet and surficial geology properties are used to estimate the travel time from a depth of three feet to ten feet. The near-surface materials sensitivity assessment was developed by estimating infiltration rates through soils and surficial geologic units based on the Natural Resources Conservation Service (NRCS) hydraulic rating (NRCS, 2009a) for soils and the geologic unit texture of deeper parent materials from Plate 3 of Part A, Surficial Geology. Estimates of infiltration rates are shown in Table 1. The NRCS defines hydraulic groups primarily based on the soil unit's texture and the presence or absence of dense, low permeability layers.

Hydraulic group A soils are more than 90 percent sand and gravel, and water is freely transmitted through the soil. Group B soils are less permeable than group A soils, but water transmission is unimpeded through the soil. In group C soils, water transmission is somewhat restricted. In group D soils, water movement is restricted or very restricted. Tipping (2006) estimated minimum transmission rates for these four soil hydraulic groups based on an NRCS web publication that is no longer available. Estimated minimum transmission rates for the surficial geologic units from Tipping (2006) were also used for this assessment.

The near-surface materials sensitivity rating is determined by using the minimum transmission rates for the soil and surficial geologic units to calculate the estimated travel time to the assumed water table depth of 10 feet. The GIS polygons from the soil survey of St. Louis County (NRCS, 2006), the soil survey of Carlton County (NRCS, 2009b), and the surficial geologic map (and the corresponding transmission rates) were combined; the total travel time to 10 feet was calculated using the soil rate for the upper three feet and the surficial geologic material rate for the lower seven feet.

The combined estimate from both layers is shown in Figure 11 as the near-surface materials geologic sensitivity. Most of the study area has an estimated infiltration travel time of 10 to 60 days (very high to moderate pollution sensitivity rating) since sand, sandy loam, and sandy till are common materials at the surface to near-surface depths, especially in the northwestern two-thirds of the study area. Estimated infiltration travel times of 61 to 510 days (low to very low pollution sensitivity rating) are very common in the southeastern portion of the study area where clay soil, and till or clayey lake sediment are the primary near-surface material. Some abrupt discontinuities of sensitivity ratings along the Carlton-St. Louis County border are due to discrepancies in the respective county soil surveys that were created at different dates by different investigators.



MAP EXPLANATION FOR FIGURE 11

Pollution sensitivity ratings for near-surface materials

Estimated vertical travel time for water-borne contaminants to move from the land surface to a depth of 10 feet.



Tritium age Color indicates tritium age of water sampled in well.

Recent—Water entered the ground since about 1953 (10 or more tritium units [TU]). Well and aquifer symbols Surficial sand aquifer. Symbols and labels

Line of cross section

Body of water.

FIGURE 11. Pollution sensitivity of the near-surface materials

GEOLOGIC ATLAS OF CARLTON COUNTY, MINNESOTA